

TM660

Dynamic
microphone head

Article-No.:
2114-001-000-03



Product:

Characteristics

- Dynamic microphone capsule
- Unidirectional noise canceling
- Chromed housing
- Designed for gooseneck mounting

Options

- Microphone preamplifier
- Black matte housing
- Mounted on gooseneck

Application range

- Radio and PA systems in mobile applications
- Designed for use in large vehicles

Accessories

- Various goosenecks and mounting brackets
- Microphone preamplifier V966, V967, V856 and V857

Scope of delivery

- Microphone head with cable

Technical Data:

General

Housing:	Brass, sand blasted chrome (matte)
Dimensions:	Length 85 mm, Ø 29 mm
Weight:	160 g (5.6 oz)
Connection:	2-wire cable shielded, 1.8 m, without connector
Storage temperature:	-25 °C to +70 °C (-13 °F to +158 °F)
Operation temperature:	-20 °C to +60 °C (-4 °F to +140 °F)

Microphone

Frequency range:	300 Hz to 8 kHz at -10 dB
Sensitivity:	1,5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance:	200 Ω ± 20 % at 1 kHz
Directivity:	Cardioid (at 1 kHz; 180° -15 dB)