

TM660 Microphone Head

Dynamic microphone head

Article Number

6114-001-100-03 (former 2114-001-000-03)



Characteristics

- Dynamic microphone capsule
- Unidirectional noise cancelling
- Chromed housing
- Designed for gooseneck mounting
- Protected against metal dust (INTERCEPT) and splash-proof

Scope of delivery

- Microphone head with cable

Options

- Microphone preamplifier
- Black housing
- Mounted on gooseneck
- [Minor modifications and individual adaptations](#) on request

Application range

- Radio and PA system in mobile applications
- Designed for use in large vehicles

Accessories

- Various goosenecks and mounting brackets
- Microphone preamplifier V966, V967, V856 and V857

Specifications

General

Housing	Brass, silver
Dimensions	Length 85 mm, Ø 29 mm
Weight	160 g (5,6 oz)
Connection	2-wire cable shielded, 3.0 m, without connector
Storage temperature	-25 °C to +70 °C (-13 °F to +158 °F)
Operating temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Certifications	DIN EN 50155:2018-05 DIN EN 45545-2:2016-02

Microphone

Frequency range	300 Hz to 8 kHz at -10 dB
Sensitivity	1.5 mV/Pa (-56 dBV/Pa ± 3 dB)
Impedance	200 Ohm ± 20 % at 1 kHz
Directivity	Cardioid (at 1 kHz; 180° -15 dB)